## LED WITH HARDENED GLASS FOR POST MOUNTING IN CAR PARKS

## **STREETPARK** LED

TOUGH, WEATHERPROOF LUMINAIRE FOR CAR PARKS AND PERIMETER AREAS

- A sleek, high quality IP65 rated LED lamp
- Adjustable for mounting onto existing 60mm diameter posts
- Osram LEDs in a hardened glass diffuser, secured by stainless steel screws into an aluminium casing



EXAMPLE PRICE: Streetpark LED standard 9200 lumen

£449.04

+VAT Including delivery

Streetpark is the hardwearing luminaire for car parks, outdoor recreation areas and perimeter lighting. An adjustable bracket allows installation on 60mm diameter posts and arms at a wide range of positions, with both symmetric and asymmetric light distribution available using special lenses. The hardened glass diffuser and frame are mounted with Allen M5 screws made of stainless steel to IP65 levels of tightness, protecting the lighting unit from moisture and dust. Colour temperatures available: 4000 K, 5000 K. LED panels (IP 67) meet the PN-EN 13201-4:2007 roads illumination requirements.
















### STREETPARK LED DIMENSIONS

STREETPARK LED PREMIUM 10500LM SYM IP65 21 750



co α= 56∞			
h[m]	Ø[m] ○	:90 α= <b>56</b> %	E <sub>AV</sub> [lux]
1	2,96		1733
2	5,93		433
3	8,89		192
4	11,8		108
5	14,8		69


















See over for specification





### STREETPARK LED PREMIUM

### LUMINAIRE DIMENSIONS



KR	A	B	C
	(mm)	(mm)	(mm)
STREETPARK LED PREMIUM	550	250	120

KR KR	blas		$\Phi$ [lm]	kg	
STREETPARK LED PREMIUM ASY 750	35 W	LED	3500	7,00	
STREETPARK LED PREMIUM ASY 750 STREETPARK LED PREMIUM SYM 750	57 W 57 W	LED LED	4700 4700	7,00 7,00	
STREETPARK LED PREMIUM ASY 750	70 W	LED	7000	7,00	
STREETPARK LED PREMIUM SYM 750	70 W	LED	7000	7,00	
STREETPARK LED PREMIUM ASY 840 STREETPARK LED PREMIUM ASY 750	105 W 113 W	LED I FD	8900 9300	7,00 7.00	
STREETPARK LED PREMIUM SYM 750	113 W	LED	9300	7,00	
STREETPARK LED PREMIUM ASY 750	105 W	LED	10500	7,00	
STREETPARK LED PREMIUM SYM 750	105 W	LED	10500	7,00	

Available colour of the light: 750/840

### LUMINAIRE OPTIONS

### CONTROL GEAR


E Driver ED DM1-10V driver EDD DM DAU driver

### DIFFUSER

SH Tempered glass SHM Tempered matt glass



### WAY OF MOUNTING








### STREETPARK LED STANDARD

### LUMINAIRE DIMENSIONS



48	A	B	C
	(mm)	(mm)	(mm)
STREETPARK LED STANDARD	550	250	120

# YR





LED



9200 17000



STREETPARK LED STANDARD SYM 757 STREETPARK LED STANDARD SYM 757

Available colour of the light: 757

### LUMINAIRE OPTIONS

### CONTROL GEAR


E Driver ED DM1-10V driver

### DIFFUSER

SH Tempered glass SHM Tempered matt glass



### WAY OF MOUNTING




















### STREETPARK LED BASIC

### LUMINAIRE DIMENSIONS



· ·			
48	A (mm)	B (mm)	C (mm)
STREETPARK LED BASIC	550	250	120









5500 11000



STREETPARK LED BASIC SYM 840 STREETPARK LED BASIC SYM 840 Available colour of the light: 840

### LUMINAIRE OPTIONS

### CONTROL GEAR


Driver

### DIFFUSER

SH Tempered glass Tempered matt glass SHM




### WAY OF MOUNTING

















For more information about STREETPARK LED call 01524 383000